

1. NANOPHYSICS

1.2. Properties of Materials and Structures

3.1.2.1. The effect of high-amplitude deformation and high-frequency magnetic field exposure on the elastic/inelastic properties of PTFE-based hybrid nanocomposite filled with Fe cluster-doped CNTs. /E. Kutelia, G. Darsavelidze, T. Dzigrashvili, D. Gventsadze, I. Kurashvili, O. Tsurtsunia, L. Gventsadze, L. Nadaraia, L. Rukhadze, T. Kukava, S. Bakhtiyarov/. Bulletin of the Georgian National Academy of Sciences. – 2021. – v. 15. – #1. – pp. 38-44. – eng.; abs.: eng., geo.

The influence of high-amplitude torsional deformation ($\epsilon \sim 10^{-1} \div 10^{-2}$) and high-frequency (2.4 GHz) magnetic field treatment on elastic/inelastic properties of PTFE-based new hybrid nanocomposites modified with a two-component filler (2.5 wt% Fe-cluster-doped CNT nanopowder + 5wt% chalcopryrite micropowder) was studied using low-frequency amplitude-independent (AIF) and amplitude-dependent (ADIF) internal friction measurements. The behavior of elastic/inelastic properties of the new trial PTFE-based hybrid nanocomposite modified by a two-component filler (Fe-cluster-doped CNTs + chalcopryrite micro-particles) was investigated in dependence on highamplitude torsional deformation ($\epsilon \sim 10^{-1} \div 10^{-2}$) and post-deformation high-frequency (2.4 GHz) magnetic field exposure and additional thermal treatment, using AIF and ADIF measurements. It is shown that self-healing of micro/nano-cracks nucleated in the deformed samples of the nanocomposite may be properly performed via their exposure to high-frequency magnetic field and the additional annealing at 200°C that leads to the recovery of the values of microplastic deformation beginning critical amplitude (ϵ_c) to the values even exceeding its initial magnitude by ~38%. Fig. 3, Tab. 2, Ref. 10.

Keywords: PTFE, hybrid nanocomposite, Fe-cluster-doped CNTs, chalcopryrite, magnetic field, internal friction

References:

1. Biswas S.K. (1992). Friction and wear of PTFE – Review. Wear. 158: 193-211.
2. Aly A.A., Zeidan El.B., Alshennawy A.A., El-Masry A.A., Wasel W.A. (2012). Friction and wear of polymer composites filled by nano-particles: a review. World Journal of Nano Science and Engineering. 2:32-39.
3. Jiabin Ye., David L. Burris and Ting Xie (2016). A review of transfer film and their role in ultra-low-wear sliding of polymers. Lubricants 4(4): 1-15.
4. Gandotra H., Mahajan S., Jandival S., Gupta S. (2018). Effect of fillers on tribological properties of PTFE: a review. International Journal of Scientific and Technical Advancements. 4 (1): 147-150.
5. Gventsadze D., Kutelia E., Nadaraia L., Padgurskas J., Gventsadze L., Tsurtsunia O. (2017). The tribological properties of PTFE modified with chalcopryrite. Proceedings of BALTRIB, 62-65, edited by J. Padgurskas. ISSN 2424-5089/e ISBN 978-609-449-093-4.
6. Kutelia E., Gventsadze D., Tsurtsunia O., Rukhadze L., Jalabadze N., Kukava T., Dzigrashvili T. (2018). Investigation of new antifrictional/frictional nanocomposites based on PTFE matrix filled with Fe-doped carbon nanoparticles. Advanced Materials Letters. 9(5): 320-325 www.iaamonline.org
7. Kutelia E., Darsavelidze G., Dzigrashvili T., Kukava T., Rukhadze L., Gventsadze L., Tsurtsunia O., Nadaraia L., Kurashvili I., Bakhtiyarov S. (2018). Internal Friction in PTFE-based nanocomposite materials filled with Fe cluster-doped CNTs. Georgian Engineering News. 87 (3): 5-13.
8. Shi Y., Feng X., Wang H., Lu X. (2007). Tribological and mechanical properties of PTFE composites filled with the combination of short carbon fiber and carbon nano-fiber. Key Engineering Materials. 334-335. 689-692.
9. Ahmed A.S., Ramanujan R.V. (2015). Curie temperature controlled self-healing magnet-polymer composites. Journal of Materials Research. 30 (7): 946-958. 10.
10. McCrum N.G. (1959). An internal friction study of polytetrafluoroethylene. Journal of Polymer Science. 34: 355-369.

3.1.2.2. Nonmonotonic carrier dispersion in dimensionally quantized nanostructures with broken symmetries. /H.S. Nikoghosyan, S.L. Harutyunyan, V.F. Manukyan, G.H. Nikoghosyan/. Proceedings of NAS RA. Physics. – 2020. – vol. 55. – #4. – pp. 537-549. – rus.; abs.: rus., arm., eng.

The features of the energy spectrum and carrier motion in one-dimensional asymmetric semiconductor nanosystems are considered. Asymmetric structures with an additional dip in the potential profile in quantum wells make it possible to vary the positions of size-quantized levels. And the additional influence of an external magnetic field leads to non-monotonic dispersion and a transverse local carrier drift. Such violations of fundamental symmetries will entail corresponding changes in the nature of electronic transitions. The dynamic properties of the electronic system of the nanostructure with the asymmetry of the quantum profile are analyzed, depending on the strength of the external magnetic field. Fig. 4, Ref. 12.

Keywords: energy spectrum, one-dimensional asymmetric semiconductor nanosystems, fundamental symmetries, quantum profile, external magnetic field

References:

1. В.В. Филиппов, А.А. Заворотный, Е.Н. Бормонтов. Конденсированные среды и межфазные границы. 13, 363 (2011).
2. М.А. Ремнев, И.Ю. Катеев, В.Ф. Елесин. ФТП. 44 1068 (2010).
3. В.П. Драгунов, И.Г. Неизвестный, В.А. Гридчин. Основы наноэлектроники. Москва. Физматкнига. 2006.
4. H.S. Nikoghosyan, S.L. Harutyunyan, V.F. Manukyan, G.H. Nikoghosyan. Physica B. 575. 411710 (2019).
5. H.S. Nikoghosyan, S.L. Harutyunyan, V.F. Manukyan, G.H. Nikoghosyan. Journal of Contemporary Physics. 54, 345, (2019).
6. Ю.А. Артамонов, А.А. Горбачевич, Ю.В. Копаев. ЖЭТФ. 101, 557 (1992).
7. А.А. Горбачевич. ЖЭТФ. 95, 1467 (1989).
8. А.А. Горбачевич, В.В. Копаев, Ю.В. Копаев. Письма в ЖЭТФ. 57, 565 (1993).
9. Л.Д. Ландау, Е.М. Лифшиц. Квантовая механика. Нерелятивистская теория. Москва. Наука. 1989.
10. А. Анималу. Квантовая теория кристаллических твердых тел. Москва. Мир. 1981.
11. В.Я. Демиховский, Г.А. Вугальтер. Физика квантовых низкоразмерных структур. Москва. Логос. 2000.
12. О.В. Кибис. Письма в ЖЭТФ. 66, 551 (1997).

3.1.2.3. Physical adsorption of single-stranded DNA on carbon nanotube. /D.G. Khechoyan, V.F. Morozov/. Proceedings of NAS RA. Physics. – 2021. – vol. 56. – #1. – pp. 100-105. – rus.; abs.: rus., arm., eng.

The results of simulation modeling of single-stranded DNA adsorption on the surface of a single-walled carbon nanotube performed by the molecular dynamics method using the GROMACS software package are presented. The dependence of the timescale and degree of DNA adsorption was studied in dependence on the chirality of the carbon nanotube and the DNA sequence. Fig. 4, Ref. 16.

Keywords: simulation, single-stranded DNA, single-walled carbon nanotube, GROMACS software package, DNA adsorption

References:

1. J. Hu, J. Shi, S. Li, Y. Qin, Z.X. Guo, Y. Song, D. Zhu. Chem. Phys. Lett. 401, 352 (2005).
2. V.N. Khabashesku, J.L. Margrave, E.V. Barrera. Diamond Relat. Mater. 14, 859 (2005).
3. D.A. Heller, et al. Science 311, 508 (2006).
4. C.L. Chen, et al. Nanotechnology 21, 095504 (2010).
5. X. Dong, D. Fu, Y. Xu, J. Wei, Y. Shi, P. Chen, L.J. Li. J. Phys. Chem. C 112, 9891 (2008).
6. M. Zheng, et al. Nat. Mater. 2, 338 (2003).
7. W. Martin, W. Zhu, G. Krilov. J. Phys. Chem. B, 112, 16076 (2008).
8. D. Pramanik, P.K. Maiti. ACS Appl. Mater. Interfaces, 9, 35287 (2017).
9. W. Cheung, et al. J. Mater. Chem., 19, 6465 (2009).

10. P.G. He, M. Bayachou. *Langmuir*, 21, 6086 (2005).
11. R.R. Johnson, A.T.C. Johnson, M.L. Klein. *Nano Lett.*, 8, 69 (2008).
12. D. Van Der Spoel, et al. *J. Comput. Chem.* 26, 1701 (2005).
13. K. Lindorff-Larsen, et al. *Proteins*. 78, 1950 (2010).
14. W.L. Jorgensen, D.S. Maxwell, J. Tirado-Rives. *J. Am. Chem. Soc.* 118, 11225 (1996).
15. H.R. Drew, et al. *Proc. Natl. Acad. Sci. USA*. 78, 2179 (1981).
16. F. Albertorio, M.E. Hughes, J.A. Golovchenko, D. Branton. *Nanotechnology*. 20 395101 (2009).

3.1.2.4. Geometric features and numerical analysis of InAsSbP composition micro- and nano-structures shape transformation at nucleation from liquid phase. /K.M. Gambaryan, V.M. Aroutiounian/. *Proceedings of NAS RA. Physics.* – 2021. – vol. 56. – #2. – pp. 208-217. – rus.; abs.: rus., eng.

Results of the characterization and numerical analysis of InAsSbP composition strain-induced micro- and nanostructures shape transition are presented. Nucleation is performed from In–As–Sb–P quaternary composition liquid phase in Stranski–Krastanow growth mode. Geometric features and the shape transformation chronology of truncated pyramidal islands, lens-shape and pyramidal quantum dots (QDs) are under consideration, which opens up new possibilities at nanoscale engineering and nanoarchitecture of several types of nanostructures. High-resolution scanning electron (HR-SEM) and transmission electron (TEM) microscopes are used for micro- and nanostructures characterization. We show that as the islands volume decreases, the following succession of shape transitions are detected: truncated pyramid, {111} faceted pyramid, {111} and partially {105} faceted pyramid, completely unfaceted “prepyramid”, which gradually evolve to hemisphere and then again to pyramidal QD but with higher facet indexes. Critical sizes of islands shape transformation from “pre-pyramid” to hemisphere (500–550 nm) and then from lens-shape again to pyramidal QDs (5–7 nm) are experimentally detected and theoretically evaluated. It is shown that theoretically calculated values coincide with experimentally obtained data. Fig. 2, Tab. 1, Ref. 21.

Keywords: numerical analysis, InAsSbP, Stranski–Krastanow growth mode, pyramidal quantum dots (QDs), truncated pyramid, faceted pyramid, pyramidal QDs

References:

1. D. Bimberg, M. Grundmann, N.N. Ledentsov. *Quantum Dot Heterostructures*. New York: Wiley. 1998.
2. P. Bhattacharya, X.H. Su, S. Chakrabarti, et al. *Appl. Phys. Lett.* 86, 191106 (2005).
3. A. Rogalski. *Acta Phys. Pol. A*. 116, 389 (2009).
4. V.M. Aroutiounian, S.G. Petrosian, A. Khachatryan, K. Touryan. *J. Appl. Phys.* 89, 2268 (2001).
5. A.M. Rudin, L.J. Guo, et al. *Appl. Phys. Lett.* 73, 3429 (1998).
6. O. Marquardt, T. Hickel, J. Neugebauer, K.M. Gambaryan, V.M. Aroutiounian. *J. Appl. Phys.* 110, 043708 (2011).
7. K.M. Gambaryan. *Nanoscale Res. Lett.* 5, 587 (2010).
8. V.M. Aroutiounian, K.M. Gambaryan, P.G. Soukiassian. *Surface Science*. 604, 1127 (2010).
9. H. Ishikuro, T. Hiramoto. *Appl. Phys. Lett.* 71, 3691 (1997).
10. K.M. Gambaryan, V.M. Aroutiounian, V.G. Harutyunyan. *Infrared Phys. & Tech.* 54, 114 (2011).
11. I. Stranski, L. Krastanow. *Math.-Naturwiss.* 146, 797 (1938).
12. K.M. Gambaryan, V.M. Aroutiounian, T. Boeck, M. Schulze. *Phys. Status Solidi C*, 6, 1456 (2009).
13. I. Daruka, J. Tersoff, A.-L. Barabasi. *Phys. Rev. Lett.* 82, 2753 (1999).
14. J. Tersoff, F.K. LeGoues. *Phys. Rev. Lett.* 72, 3570 (1994).
15. M. Zinke-Allmang, L.C. Feldman, M.H. Grabow. *Surf. Sci. Rep.* 16, 377 (1992).
16. F.M. Ross, J. Tersoff, R.M. Tromp. *Phys. Rev. Lett.* 80, 984 (1998).
17. J. Tersoff, B.J. Spencer, A. Rastelli, H. von Kanel. *Phys. Rev. Lett.* 89, 196104 (2002).

18. N. Liu, J. Tersoff, O. Baklenov, A.L. Holmes, Jr., C.K. Shih. Phys. Rev. Lett. 84, 334 (2000).
19. K.M. Gambaryan, V.M. Aroutiounian, T. Boeck, et al. J. Phys. D: Appl. Phys. 41, 162004 (2008).
20. J. Tersoff, R.M. Tromp. Phys. Rev. Lett. 70, 2782 (1993).
21. K.L. Safonov, V.G. Dubrovskii, N.V. Sibirev, Yu.V. Trushin. Technical Physics Letters 33, 490 (2007).

3.1.2.5. Monovalent and divalent impurity states in a semiconductor nanoplatelets. /V.A. Harutyunyan, H.A. Sarkisyan/. Proceedings of NAS RA. Physics. – 2021. – vol. 56. – #3. – pp. 348-355. – rus.; abs.: rus., arm., eng.

Within the framework of the variational method, hydrogen-like impurity states in the semiconductor nanoplatelets with the shape of a rectangular parallelepiped of a small thickness are investigated. Due to the small thickness of the nanostructure, it is shown that, the impurity can be considered two-dimensional. In the case of a divalent impurity, the electron-electron interaction is also considered two-dimensional and taken into account as a perturbation. By the analogy with the theory of the helium atom, the electron-electron interaction energy is determined for the para-state. Fig. 4, Ref. 16.

Keywords: variational method, semiconductor nanoplatelets, nanostructure, divalent impurity, helium atom, electron-electron interaction

References:

1. A.O. Bochkarev, M.A. Grekov. Physical Mesomechanics. 22, 209 (2019).
2. B. Karami, S. Karami. Advances in nano research. 7, 51 (2019).
3. E.V. Shornikova et al. Nano letters, 20, 1370 (2020).
4. B. Jin, H. Wang, M.L. Sushko, C. Jin, R. Tang. Nanoscale. 12, 19592 (2020).
5. D. Xiang, Y. Li, L. Wang, Y. Zhao, K. Wu. ACS Photonics. 8, 745 (2021).
6. D.A. Baghdasaryan, E.M. Kazaryan, H.A. Sarkisyan, K.D. Moiseev. Physica E. 90, 170 (2017).
7. Y. Yanget al. IEEE Transactions on Nanotechnology. 18, 220 (2019).
8. A.G. Vitukhnovsky et al. Chem. Phys. Letters. 619, 185 (2015).
9. J. Planelles.Theor. Chem. Acc. 136, 81 (2017).
10. Л.Г. Мардоян, Г.С. Погосян, А.Н. Сисакян, В.М. Тер-Антонян. Теоретическая и математическая физика. 66, 99 (1984).
11. Д.Б. Айрапетян, Э.М. Казарян, О.Х. Тевосян. Изв. НАН Армении. Физика. 49, 190 (2014).
12. О.Х. Тевосян. Изв. НАН Армении. Физика. 47, 427 (2012).
13. Р.Г. Погосян. Изв. НАН Армении. Физика. 49, 114 (2014).
14. A.K. Manaselyan, A.V. Ghazaryan, A.A. Kirakosyan. J. Contemp. Phys. 43, 211 (2008).
15. A.K. Manaselyan, A.V. Ghazaryan, A.A. Kirakosyan. J. Contemp. Phys. 45, 269 (2010).
16. T.A. Sargsian. J. Contemp. Phys. 54, 168 (2019).

3.1.2.6. Electrical characteristics and photoresponse of the "carbon nanofilm on silicon" heterostructure. /G. A. Dabaghyan, L.M. Matevosyan, K.E. Avjyan/. Proceedings of NAS RA. Physics. – 2021. – vol. 56. – #3. – pp. 374-383. – rus.; abs.: rus., eng.

The electrical characteristics and photoresponse of the “carbon nanofilm on silicon” heterostructure obtained by pulsed-laser deposition, where the thickness of the carbon nanofilm is selected from the condition of the maximum antireflection effect of the substrate, have been investigated. It was found that the obtained heterostructure is rectifying with a rectifying coefficient of 35 at 1 V. The direct current-voltage characteristic from 0.1 V to 0.35 V is in satisfactory agreement with the expression $J = J_0 \exp(eU/\eta kT)$. An increase in the voltage in the forward direction leads to the appearance of the space charge-limited currents ($J = AU^2$). Linearization of the $C^{-2} - U$ dependence indicates the sharpness of the impurity distribution in the space charge region. The mechanism of the photoresponse of the

heterostructure is similar to the photoresponse of anisotype heterostructures with the “window” effect. The longwavelength edge (1.1 μm) of the photosensitivity is determined by the silicon substrate, and absorption in the carbon nanofilm leads to an additional expansion of the photosensitivity region. The heterostructure has uniform photosensitivity at the level 0.8 of a relative photoresponse in the wavelength range of 0.55–1.1 μm . The short-wavelength tail reaches up to 0.4 μm . Fig. 8. Ref. 17.

Keywords: “carbon nanofilm on silicon” heterostructure, maximum antireflection effect of the substrate, space charge-limited currents, short-wavelength tail

References:

1. A.G. Milnes, D.L. Feucht. Heterojunctions and Metal-Semiconductor Junctions. New York. London: Academic press. 1972, 418 p.
2. L.S. Lunin, M.L. Lunina, O.V. Devitsky, I.A. Sysoev. Semiconductors. 51(3), 387 (2017).
3. D.S. Da Silva, A.D.S. Côrtes, M.H. Oliveira Jr., E.F. Motta, G.A. Viana, P.R. Mei, F.C. Marques. Journal of Applied Physics. 110, 043510 (2011).
4. R. Hauert. Diamond and Related Materials. 12, 583 (2003)
5. A.C. Ferrari. Surface and Coatings Technology. 180-181, 190 (2004)
6. K.E. Avjyan, L.A. Matevosyan, K.S. Ohanyan, L.G. Petrosyan. Instruments and Experimental Techniques. 59(1), 60 (2016).
7. Z.Q. Ma, B.X. Liu. Solar Energy Materials & Solar Cells. 69, 339 (2001)
8. S.V. Gaponov, A.A. Gudkov, E.V. Klunokov, M.D. Strikovskij. Sov. Electronnaja Promishlennost. 5-6, 110 (1981).
9. J.C. Miller. Laser Ablation – Principles and Applications, Berlin: Springer-Verlag. 1994
10. R. Eason. Pulsed Laser Deposition of Thin Films. John Wiley & Sons. 2006
11. A.G. Alexanian, N.S. Aramyan, K.E. Avjyan, A.M. Khachatryan, R.P. Grigoryan, A.S. Yeremyan. Technology of PLD for photodetector materials. in: Combinatorial and High-Throughput Discovery and Optimization of Catalysts and Materials. edited by R.A. Potirailo and W.F. Maier. CRC/Taylor & Francis. 2006.
12. S. Nakano, T. Matsuoka, S. Kiyama, et al. Jpn. J. Appl. Phys. 25(12), 1936 (1986)
13. A.D. Compaan, I. Matulionis, S. Nakade. Opt. Lasers Eng. 34(1), 15 (2000).
14. D. Bäuerle. Laser Processing and Chemistry. 3rd ed. Berlin: Springer. 2000.
15. Y. Miyajima, S.J. Henley, G. Adamopoulos, V. Stolojan, E. Garcia-Caurel, B. Drévillon, J.M. Shannon, S.R.P. Silva. Journal of Applied Phys. 105, 073521 (2009).
16. H. Yasuda, R. Matsuno, N. Koito, H. Hosoda, T. Tani, M. Naya. Appl. Phys Lett. 111, 231105 (2017). 17. B. Fan, K. Nose, D. Diao, T. Yoshida. Appl. Surface Science. 273, 816 (2013).

3.1.2.7. Investigation of properties of graphene quantum dots and carbon nanotubes synthesized in a colloid solution. /N.B. Margaryan, N.E. Kokanyan, E.P. Kokanyan/. Proceedings of NAS RA. Physics. – 2021. – vol. 56. – #3. – pp. 392-398. – rus.; abs.: rus., eng.

In this paper, a simple and effective method for the synthesis of carbon nanotubes, graphene-based quantum dots is described. The topological properties of these nanostructures are studied by atomic force and scanning electron microscopes. The potential of quantum dots is investigated by the Kelvin probe method. To study the formed bonds and for a detailed structural analysis, Raman spectroscopy is performed. Other self-organized structures based on graphene are also disclosed using Raman spectroscopy. The effect of photon-phonon scattering on the Raman scattering spectrum is discussed. Fig. 4, Ref. 26.

Keywords: synthesis of carbon nanotubes, graphene-based quantum dots, Kelvin probe method, Raman spectroscopy, photon-phonon scattering

References:

1. N.B. Margaryan, N.E. Kokanyan, E.P. Kokanyan. Journal of Saudi Chemical Society. 23, 13 (2019).
2. I. Levchenko, S. Xu, G. Teel, D. Mariotti, M.L.R. Walker, M. Keidar. Nat. Commun. 9, art. numb. 879 (2018).
3. J. Chen, C. Li, G. Shi. Phys. Chem. Lett. 4, 1244 (2013).
4. I. Levchenko, K. Bazaka, Y. Ding, et al. Appl. Phys. Rev. 5, 011104 (2018).
5. F. Perrozzi, S. Prezioso, L. Ottaviano. J. Phys.: Condens. Matter. 27, 013002 (2014).
6. L.A. Ponomarenko, F. Schedin, M.I. Katsnelson, et. al. Science. 320, 356 (2008).
7. K. Geim, K.S. Novoselov. Nat. Mater. 6, 183 (2007).
8. M.Y. Han, B. Ozyilmaz, Y. Zhang, P. Kim. Phys. Rev. Lett. 98, 206805 (2007).
9. D. Pan, J. Zhang, Z. Li, M. Wu. Adv. Mater. 22, 734 (2010).
10. W. Qian, T. Liu, F. Wei, H. Yuan. Carbon. 41. 1851 (2003).
11. M.S. Dresselhaus, G. Dresselhaus, R. Saito, A. Jorio. Phys. Rep. 409, 47 (2005).
12. J. Zhao, M. Shaygan, J. Eckert, M. Meyyappan, M.H. Rummeli. Nano Lett. 14, 306 (2014).
13. S. Haar, M. Bruna, J.X. Lian. J. Phys. Chem. Lett. 7, 2714 (2016).
14. A.S. Pavlova, E.A. Obratsova. J. Nanophotonics. 10(1), 012525 (2016).
15. J. Chen et al. FlatChem. 5, 25 (2017).
16. K. Safarova, A. Dvorak, R. Kubinek, M. Vujtek, A. Rek. Modern Research and Educational Topics in Microscopy. 513, Formatex. 2007.
17. N. Margaryan. J. Phys. Sci. Appl. 7(2), 46 (2017).
18. M. Massicotte et al. Nanotechnology. 24, 325601 (2013).
19. S. Costa, E. Borowiak-Palen, M. Kruszyńska, A. Bachmatiuk, R.J. Kaleńczuk. Materials Science Poland. 26(2), 433 (2008).
20. J. Wu, P. Wang, F. Wang, Y. Fang. Nanomaterials. 8, 864 (2018).
21. L. Bokobza, J. Zhang. eXPRESS Polymer Letters. 6(7), 601 (2012).
22. N. Lang, W. Kohn. Physical Review B. 3(4). 1215 (1971).
23. A. Nazarov et al. Phys. Status Solidi C. 10 (7–8). 1172 (2013).
24. R. Arenal, A.C.Y. Liu. Appl. Phys. Lett. 91. 211903 (2007).
25. J.L. Koenig. Analytical Chemistry. 65(1). 207 (1999).
26. A. Niilisk et al. Carbon. 98, 658 (2016).

3.1.2.8. Physicomechanical properties of nanocomposites based on copolymers of ethylene with α -olefins and clinoptilolite. /N.T. Kakhramanov, I.V. Bayramova, V.S. Osipchik, A.D. Ismayilzade, S.R. Abdalova, I.A. Ismayilov, U.V. Namazli/. Azerbaijan Chemical Journal. – 2020. – #4. – pp. 22-27. – eng.; abs.: eng., az., rus.
DOI: <https://doi.org/10.32737/0005-2531-2020-4-22-27>

The results of studying the effect of clinoptilolite concentration on the properties of nanocomposites based on of ethylene with butylene and of ethylene with hexene copolymer are presented. The effect of clinoptilolite particle size on ultimate tensile stress, elongation at break, flexural modulus, heat resistance, and melt flow index of composites was studied. It is shown that nanocomposites based on ethylene copolymers are characterized by higher values of physicomechanical properties. The additional use of ingredients such as alizarin and calcium stearate contributes to a significant improvement in the complex of properties of nanocomposites based on ethylene copolymers and clinoptilolite. Tab. 3, Ref. 12.

Keywords: ultimate tensile stress, elongation at break, heat resistance, flexural modulus, composite, copolymer

References:

1. Berlin A.A., Volfson S.A., Oshman V.G. Principy sozdaniya kompozicionnyh materialov. M.: Himija. 1990. 240 s.

2. Ermakov S.N., Kerber M.L., Kravchenko T.P. Himicheskaja modifikacija i smeshenie polimerov pri reakcionnoj jekstruzii. *Plasticheskie massy*. 2007. No 10. S. 32–41.
3. Kakhramanov N.T., Ismailzade A.D., Arzumano N.B., Mammadli U.M., Martinova Q.S. Filled composites based on polyolefins and clinoptilolite. *American Scientific Journal*. 2016. No 4. V. 4. P. 60–65.
4. Stegno E.V., Lalajan V.M., Grachev A.V., Vladimirov L.V., Berlin A.A. Svojstva gibridnyh smesey polioksida bora i sopolimera jetilena s vinilacetatom. *Enciklopedicheskij slovar*. 2018. No 5. S. 1–7.
5. Kakhramanov N.T., Kurbanova R.V., Koseva N.S., Gahramanly Ju.N., Mamedli U.M. Gibridnye nanokompozity na osnove polipropilena i klinoptilolita. *Plast. massy*. 2019. No 3. V. 4. S. 32–34.
6. Kakhramanov N.T., Kurbanova R.V. Gibridnye nanokompozity na osnove funkcionalizirovannogo polijetilena vysokoj plotnosti i appretirovannogo bentonita. *Enciklopedicheskij spravocnik*, 2019. No 7. S. 17–25.
7. Kalinchev Je.L., Sakovceva M.B., Pavlova I.V., Kavokin E.I., Sakovich D.A. Effektivnyj podhod k sozdaniju sovremennyh polimernyh kompozicionnyh materialov. *Polimer. materialy*. 2008. No 3. S. 4–14.
8. Sirota A.G., Bugorkova V.S. Ob effektivnosti poljarnyh modificirujushhih dobavok k polietilenu. *Plasticheskie massy*. 2010. No 5. S. 6–11.
9. Kakhramanov N.T., Azizov A.G., Osipchik V.S. Nanostrukturirovannye kompozity polimerno materialovedenie. *Plasticheskie massy*. 2016. No 1. V. 2. S. 49–57.
10. Cherdynceva S.V., Belousov S.I., Krashennnikov S.V. Vlijanie vida organicheskogo modifikatora montmorillonita na fiziko-himicheskie svojstva nanokompozitov na osnove poliamida-6, poluchennyh smesheniem v rasplave. *Plast. massy*. 2013. No 5. S. 39–43.
11. Kakhramanov N.T., Gasimova G.Sh., Pesetsriy S.S., Kakhramanly Y.N., Gurbanova R.V., Hajiyeve R.Sh., Suleymanova E.I. Physical and mechanical properties of nanocomposites based on block copolymer propylene with ethylene and graphite. *Chemical problems*. 2019. No 1. S. 72–80.
12. Kakhramanov N.T., Bajramova I.V., Koseva N.S., Gadzhieva R.Sh. Fiziko-mehaniicheskie svojstva kompozitov na osnove vezuviana i sopolimera jetilena s butilenom. *Perspektivnye materialy*. 2019. No 3. S. 47–53.

3.1.2.9. Copper-containing nanocomposites on the basis of isotactic polypropylene and butadiene-nitrile rubber. /T.M. Gulieva/. *Azerbaijan Chemical Journal*. – 2021. – #3. – pp. 38-42. – eng.; abs.: eng., az., rus.

DOI: <https://doi.org/10.32737/0005-2531-2021-3-38-43>

The influence of additives of nanofillers containing nanoparticles of copper oxides stabilized by a polymer matrix of maleinized high-pressure polyethylene obtained by the mechano-chemical method on the structure and properties features of metal-containing nanocomposites based on isotactic polypropylene and butadienenitrile rubber by X-ray phase and differential thermal analyses is studied. The improvement of strength, deformation and rheological parameters, as well as thermal-oxidative stability of the obtained nanocomposites was revealed, that is probably due to the synergistic effect of interaction of copper-containing nanoparticles with maleic groups of maleinated high-pressure polyethylene. It is shown that nanocomposites based on isotactic polypropylene and butadiene-nitrile rubber can be processed both by pressing method and by injection molding and extrusion methods. The prospects of using a nanofiller containing NPs of copper oxide stabilized by a high-pressure polyethylene matrix obtained by the mechanochemical method as an additive to TPE based on PP/BNR is shown to contribute to the creation of a fine-crystalline structure of the composition, and therefore its properties are improved and thereby expand scope of the obtained nanocomposite. Fig. 4, Tab. 1, Ref. 18.

Keywords: isotactic polypropylene, butadiene-nitrile rubber, metal-containing nanocomposites, copper oxide nanoparticles, maleinized high-pressure polyethylene, thermal properties, XRD, SEM analyses

References:

1. Polymer blends / Ed. D. Paul and S. Newman. M.: Mir, 1981.V. 2. P. 312–338.

2. Abdou-Sabet S., Datta S. *Polymer Blends* / Ed. by D.R. Paul, C.B. Bucknall. New York; Chichester; Weinheim; Brisbane; Singapore; Toronto: Wiley, 2000. 1224 p.
3. Holden G. *Elastomers, thermoplastic*. Encyclopedia of polymer science and technology. 12 volumes. Ed. by H.F. Mark. V. 6. John Wiley & Sons, 2004. P. 63–88.
4. Ashpina O. *TEP Trends The Chemical J.* 2011. N 1. P. 58–61.
5. Magerramov A.M., Kurbanova N.I., Bayramov M.N., Alimirzoyeva N.A., Ragimova S.K., Nabiyeva A.N. Osobennosti radiotermolyuminesentsii kompozitsiy polipropilena i etilenpropilendiyenovogo elastomera SKEPT-4044 s nanorazmernymi metallosoderzhashchimi napolnitelyami. *Fizika i khimiya obrabotki materialov*. 2020. № 3. S. 66–73.
6. Kakhramanov N.T., Guliyev A.D., Pesetskiy S.S. Dinamicheski vulkanizovannyye nanokompozity na osnove random polipropilena, butadiyen-nit- ril'nogo kauchuka i kaolina. *Kompozity i nanostruktury*. 2019. № 4. S. 131–136.
7. Guseynova Z.N., Kakhramanov N.T., Mamedov B.A., Osipchik V.S., Mamedli U.M. Termoelastoplasty na osnove termoplastichnykh poliolefinov i butilkauchuka. *Perspektivnyye materialy*. 2018. № 7. S. 33–42.
8. Kurbanova N.I., Alimirzoyeva N.A., Kuliyeu A.M., Guseynova Z.N., Ishenko N.Ya. Metal-containing nanocomposites on the basis of isotactic polypropylene, *Inorganic Materials: Applied Research*. 2019. V. 10. No. 2. P. 411–415.
9. Perestoronina Z.A., Ableyev R.I., Baranets I.V., Kurlyand S.K. Vliyaniye polimernykh dobavok na usileniye mezhfaznogo vzaimodeystviya v smesevykh termoelastoplastakh Kauchuk i rezina. 2012. № 2. S. 13–16.
10. Zaikin, A.E., Bobrov G.B. Compatibilization of polypropylene and butadiene–acrylonitrile rubber using an organic peroxide and an oligoether acrylate. *Russian J. Applied Chemistry*. 2015. V. 88. No. 5. P. 800–807.
11. Wolfson S.I., Okhotina N.A., Nigmatullina A.I., Sabirov R.K., Kuznetsova O.A., Akhmerova L.Z. Elastic-hysteretic properties of dynamic thermoplastic elastomers modified by nanofiller. *Plast. masses*. 2012. No 4. P. 42–45.
12. Mikhaylin Yu.A. Polymer nanocomposite materials. *Polymer materials*. 2009. No. 7. P. 10–13.
13. Pomogailo A.D., Rosenberg A.S., Uflyand I.E. *Metal nanoparticles in polymers*. Moscow: Chemistry, 2000. 672 p.
14. Gubin S.P., Yurkov G.Yu., Kosobudsky I.D. Nanomaterials based on metal-containing nanoparticles in polyethylene and other carbon-chain polymers. *International. J. Materials and Product Technology*. 2005. V. 23. N 1-2. P. 2–25.
15. Guliyeva T.M., Kurbanova N.I. Obtaining and study of the structure and properties of metalcontaining nanoparticles in the matrix of maleinized polyethylene. *Gənc tədqiqatçı*. 2019. V cild. № 2. P. 93–98.
16. Pomogailo A.D. Molecular polymer-polymer composition. *Synthetic aspects Advances in chemistry*. 2002. V. 71. № 1. P. 5–38.
17. Kuleznev V.N. *Smesi i splavy polimerov. Konspekt lektsiy*. SPb.: Nauchnyye osnovy tekhnologii. 2013. 216 s.
18. Kakhramanly Yu.N. *Nesovmestimyye polimernyye smesi i kompozitsionnyye materialy na ikh osnove*. Baku: Elm, 2013. 152 s.

3.1.2.10. Copper-containing nanocomposites based on isotactic polypropylene and high pressure polyethylene. /S.K. Ragimova/. *Azerbaijan Chemical Journal*. – 2021. – #3. – pp. 49-53. – eng.; abs.: eng., az., rus.

DOI: <https://doi.org/10.32737/0005-2531-2021-3-49-53>

The effect of nanofilles additives containing copper oxide nanoparticles stabilized by a polymer matrix of high-pressure polyethylene obtained by the mechanochemical method on features of the structure and properties of metal-containing nanocomposites based on isotactic polypropylene and high-pressure polyethylene was studied using differential thermal (DTA) and X-ray phase (XRD) analyzes. The improvement of strength, deformation and rheological parameters, as well as thermal-oxidative stability of the obtained nanocomposites was revealed, that apparently, is associated with the synergistic effect of

interfacial interaction of copper-containing nanoparticles in the PE matrix with the components of the PP/PE polymer composition. Fig. 2, Tab. 2, Ref. 19.

Keywords: isotactic polypropylene, high pressure polyethylene, copper oxide nanoparticles, thermal properties, DTA and XRD analysis

References:

1. Ermakov S.N., Kravchenko T.P. Polymer compatibility. Thermodynamic and chemical aspects. Plast. Mass. 2012. No. 4. P. 32–38.
2. Novokshonov V.V., Musin I.N., Kimbelblat V.I. Dependence of the properties of PP/EPR mixtures on the composition and characteristics of polymers. Plast. mass. 2009. No 5. P. 7–10.
3. Kuchmenova L.Kh., Slonov A.L., Zhansitov A.A., Shelgaev V.N., Khashirova S.Yu., Mikitaev A.K. The study of the thermal properties of polymerpolymer compositions based on PP. Plast. mass. 2014. No 7–8. P. 7–9.
4. Nigmatulina A.I., Volfson S.I., Okhotina N.A., Shaldybina M.S. Svoystva dinamicheskikh termoelastoplastov, soderzhashchiy modifitsirovanny polipropilen i sloisty napolnitel. Vestn. Kazan. tekhnol. un-ta. 2010. № 9. S. 329–331.
5. Perestoronina Z.A., Ableyev R.I., Baranets I.V., Kurlyand S.K. Vliyaniye polimernykh dobavok na usileniye mezhfaznogo vzaimodeystviya v smesevykh termoelastoplastakh. Kauchuk i rezina. 2012. № 2. S. 13–16.
6. Zaikin A.Ye., Bobrov G.B. Maslostoykiy termoelastoplast na osnove smesi polipropilena i sopolimeraetilena s vinilatsetatom, vulkanizirovanny 53 po reaktsii gidrosilirovaniya. Vest. Kazan. Tekhnol. un-ta. 2013. T. 16. № 2. S. 105–108.
7. Kakhramanov N.T., Guliyev A.D., Pesetskiy S.S. Dinamicheski vulkanizovannyye nanokompozity na osnove random poliproplena, butadiyen-nitril'nogo kauchuka i kaolina. Kompozity i nanostruktury. 2019. № 4. S. 131–136.
8. Sevastyanov D.V., Doriomedov M.S., Daskovsky M.I., Skripachev S.Yu. Self-reinforced polymer composites classification, preparation, mechanical properties and applications (review). Electronic scientific journal "VIAM Works". 2017. No 4. P. 104–118.
9. Mikhaylin Yu.A. Polymer nanocomposite materials. Polymer materials. 2009. No 7. P. 10–13.
10. Tretyakov A.O. Polymer nanocomposites are materials of the 21st century. Equipment and tools for professionals. 2003. No 2 (37). P. 18–20.
11. Foster L. Nanotechnology. Science, innovation and opportunity. M.: Technosphere. 2008. 352 p.
12. Pomogailo A.D., Rosenberg A.S., Uflyand I. E. Metal nanoparticles in polymers. M.: Chemistry. 2000. 672 p.
13. Gubin S.P., Yurkov G.Yu., Kosobudsky I.D. Nanomaterials based on metal-containing nanoparticles in polyethylene and other carbon-chain polymers. Int. J. Materials and Product Technology. 2005. V. 23. № 1–2. P. 2–25.
14. Kurbanova N.I., Kuliyeu A.M., Alimirzoeva N.A., Aliyev A.T., Ishenko N.Ya., Nurullayeva D.R. Preparation of copper-containing nanoparticles in polyethylene matrix without use of solvents. Science and Technology of Polymers and Advanced Materials: Applied Research Methods. Editor(s): O.V. Mukbaniani, T.N. Tatrishvili, M.J.M. Abadie to be published by Apple Academic Press. 2019. P. 57–65.
15. Ragimova S.K. Obtaining the metal-containing nanoparticles in polyethylene matrix by mechanochemical method and study of their properties. Azerb. Chem. J. 2020. No 2. P. 20–25.
17. Tekhnicheskkiye svoystva polimernykh materialov: Uchebno-spravochnoye posobiye. Pod obshchey red. prof. V.K. Kryzhanovskogo. SPb: Professiya. 2007. 240 s.
18. Pomogailo A.D. Molecular polymer-polymer compositions. Synthetic aspects. Advances in chemistry. 2002. V. 71. № 1. P. 5–38.
19. Kuleznev V.N. Smesi i splavy polimerov. Konspekt lektsiy. SPb.: Nauchnyye osnovy iologii. 2013. 216 s.
20. Kakhramanly Yu.N. Nesovmestimyye polimernyye smesi i kompozitsionnyye materialy na ikh osnove. Baku: Elm, 2013. 152 s.